

Appl. No. 09/899,095

Reply to Office Action of September 8, 2003

Atty. Docket: 1602-0173P

13- 205
8050

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A door glass run attached to a door sash of a vehicle for sealing between said door sash and a door glass having a first surface and second surface, comprising:

a door glass run body, formed into having a substantially
5 substantial U-shaped cross section which has a first side portion,
a second side portion and a bottom face portion;

a pair of lip portions with each one of the lip portion first
lip extending from opposite sides of an opening edge of said door
glass run body an edge of the first side portion toward a said
bottom face portion of said door glass run body and slidably
contacting with the first surface of said door glass; and

a second lip extending from an edge of the second side portion
toward said bottom face portion and slidably contacting with the
second surface of said door glass, wherein

one a length of said first lip portion of said pair of lip
portions has a length is set so that, when other lip portion of

Appl. No. 09/899,095
 Reply to Office Action of September 8, 2003
 Atty. Docket: 1602-0173P

~~said pair of lip portions is bottomed with said door glass run body, the one said door glass is in a position where said door glass presses said second lip against said second side~~ ^(portion surface)
~~said first lip portion~~ ^{is} ~~may not be~~ ^{1st surface of said} spaced away from said door glass,

~~and the other length of said second lip portion has a length~~ ^{is} ~~set so that, when the one lip portion is brought into contact with said door glass run body, the other lip portion~~
~~said door glass is in a position where said door glass presses said first lip against said first side portion, said second lip~~ ^{is} ~~not~~
~~spaced away from said door glass.~~ ^{the 2nd surface of}

~~at least one of said lips includes a concave notch portion at a base end portion~~ ^{here of} ~~and a depth of said concave notch portion is set equal to or less than 0.5 mm.~~

2. (Currently Amended) A door glass run attached to a door sash of a vehicle for sealing between said door sash and a door glass having a first surface and second surface, comprising:

a door glass run body, formed into having a substantially substantial U-shaped cross section which has a first side portion, a second side portion and a bottom face portion; and

~~a pair of lip portions with each one of the lip portions~~ first lip ~~extending from opposite side of an opening edge of said door~~

Appl. No. 09/899,095
Reply to Office Action of September 8, 2003
Atty. Docket: 1602-0173P

~~glass run body~~ an edge of the first side portion toward a said
bottom face portion of said door glass run body and slidably
contacting with the first surface of said door glass; and

a second lip extending from an edge of the second side portion
toward said bottom face portion and slidably contacting with the
second surface of said door glass, wherein

~~a protrusion being provided on an inner wall face of said door~~
~~glass run body and contacting with at least one of said lip~~
~~portions on its rear face; at least one of said side portions~~
includes a protrusion facing said lip extending from said at least
one side portion,

a height of said protrusion having a height is set so that,
when said door glass vibrates, an ⁹last-named lip is pressed against
said protrusion, a tip end portion of said at least one of the lip
portions last-named lip does not contact with said door glass run
body side portion including said protrusion,

~~said protrusion is disposed at a position nearer to a base end~~
~~portion of the at least one of said lip portions compared to a~~
~~position at which the lip portion and said door glass contact with~~
~~each other,~~

and a tip end of said protrusion is disposed so that said lip
portion does not contact with said door glass at a position nearer

~~to said base end portion compared to said protrusion and said lip~~
~~portion contact with each other~~in a region between a part of said
last-named lip which contacts with said door glass and a base end
portion of last-named lip and not including said part of said last-
named lip.

3. (Canceled)

4. (Currently Amended) The door glass run as claimed in
claim 2, wherein ~~one~~a length of said first lip portion of said
~~pair of lip portions has a length~~this set so that, when ~~the other lip~~
~~portion of said pair of lip portions is bottomed with said door~~
~~glass run body~~door glass is in a position where said door glass
presses said second lip against said second side portion, the
~~one~~said first lip portion may not be spaced away from said door
glass,

and ~~the other~~a length of said second lip portion has a
~~length~~this set so that, when ~~the one lip portion is bottomed with~~
~~said door glass run body~~said door glass is in a position where said
door glass presses said first lip against said first side portion,
~~the other lip portions~~said second lip may not be spaced away from
said door glass.

Appl. No. 09/899,095
Reply to Office Action of September 8, 2003
Atty. Docket: 1602-0173P

5. (Canceled)

6. (Canceled)

7. (Currently Amended) The door glass run as claimed in claim 2, wherein at least one of said lips includes a concave notch portion ~~is formed and defined by an inner wall face between at a base end portion, of at least one of the lip portions and said inner wall face of said door glass run body~~

~~and the~~ a depth of said concave notch portion has a depth ~~this~~ set equal to or smaller than a predetermined depth.

8. (Canceled)

9. (Currently Amended) The door glass run as claimed in claim 4, wherein at least one of said lips includes a concave notch portion ~~is formed and defined by an inner wall face between at a base end portion of at least one of the lip portion and said inner wall face of said door glass run body,~~ and ~~the~~ a depth of said concave notch portion has a depth ~~this~~ set equal to or smaller than a predetermined depth.

10. (Canceled)

11. (Canceled)

Appl. No. 09/899,095
Reply to Office Action of September 8, 2003
Atty. Docket: 1602-0173P

12. (Original) The door glass run as claimed in claim 7, wherein the depth of said notch portion is set equal to or less than 0.5 mm.

13. (Canceled)

14. (Canceled)

15. (Canceled)

16. (Canceled)

17. (Canceled)

18. (Currently Amended) The door glass run as claimed in claim ~~11~~1, wherein the depth of the notch portion is equal to 0.5 mm.

19. (Currently Amended) The door glass run as claimed in claim 7, wherein the depth of the notch portion is equal to 0.5 mm.

20. (Canceled)

21. (Currently Amended) The door glass run as claimed in claim 9, wherein the depth of the notch portion is equal to 0.5 mm.

22. (Canceled)

Appl. No. 09/899,095
Reply to Office Action of September 8, 2003
Atty. Docket: 1602-0173P

23. (Previously Presented) The door glass run as claimed in claim 9, wherein the depth of said concave notch portion is set equal to or less than 0.5 mm.

24. (New) A door glass run attached to a door sash of a vehicle for sealing between said door sash and a door glass having a first surface and second surface, comprising:

a door glass run body, formed into a substantial U-shaped cross section which has a first side portion, a second side portion and a bottom face portion;

a first lip extending from an edge of the first side portion toward said bottom face portion and slidably contacting with the first surface of said door glass; and

a second lip extending from an edge of the second side portion toward said bottom face portion and slidably contacting with the second surface of said door glass, wherein

said first portion includes a first protrusion facing said first lip,

a height of said first protrusion is set so that, when said first lip is pressed against said first protrusion, a tip end

Appl. No. 09/899,095
Reply to Office Action of September 8, 2003
Atty. Docket: 1602-0173P

portion of said first lip does not contact with said first side portion,

and a tip end of said first protrusion is disposed in a region between a part of said first lip which contacts with the first surface of said door glass and a base end portion of said first lip and not including said part of said first lip.

25. (New) The door glass run as claimed in claim 24, wherein said second portion includes a second protrusion facing said second lip,

a height of said second protrusion is set so that, when said second lip is pressed against said second protrusion, a tip end portion of said second lip does not contact with said second side portion,

and a tip end of said second protrusion is disposed in a region between a part of said second lip which contact with the second surface of said door glass and a base end portion of said second lip and not including said part of said second lip.